

IDXPERT™ Handheld Labeler



More Options, More Brains, More Brawn...Less Waste.



More Types of Labels

- Colored Continuous tapes for pipe markers, equipment ID and safety warnings
- PermaSleeve™ wire marker sleeves
- Self-Laminating wire & cable markers
- Terminal Block markers
- Patch Panel markers
- Face Plate & Outlet markers
- General-purpose die-cut labels

More Sizes

- Prints from .06" up to 1.25" characters on label stock up to 1.5" wide

More Symbols

- Code 39 bar codes
- 82 Symbols including electrical, voice/data, safety & protection, warning, and machine & operational

More Brains

- Drop Lock & Go™ Smart Cartridges™ are fast to install and remove
- Electronically pre-calibrated to orient the label just the way you need it with no special keys to press
- Memory to store frequently used set-ups

Prints Clean & Fast

- Users of dot-matrix printers will benefit from crisp, non-smearing thermal transfer print quality, faster print speed and more text-editing and symbols capabilities

Less Waste

- Edge-to-edge printing on continuous tapes so you don't pay for unused label material
- Die-cut labels are pre-cut to the size you need—no waste
- Runs on 6 AAs or optional AC

Two printer layouts—identical functionality and supplies.

Catalog No.	Description
XPERT-ABC	Printer*(ABC Layout)
XPERT-HC-ABC	Hard Case for ABC Layout
XPERT-KEY	Printer*(KEYBOARD Layout)
XPERT-HC-KEY	Hard Case for KEYBOARD Layout
XPERT-AC	AC Adapter
PCCABLE-1	Spare PC Cable for Upgrades Only
PCK-4	Cleaning Kit

*Printer ships with: Hard Case, 1.5" Cont. Tape, Product CD



Indoor/Outdoor Grade Facility & Safety Labels

This indoor/5 year outdoor vinyl is very pliable and conforms well to smooth or rough surfaces such as pipes, walls, doors, panels, shelving, bins and equipment. Aggressive permanent adhesive. Excellent resistance to oils, detergents, dirt, grime and many solvents.

- B-580 Indoor/Outdoor Vinyl material
- Permanent adhesive, good for rough surfaces
- Temp Range -40°F to 248°F (-40C to 120C)

Coming Soon!

Diagram




Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
			A	B	A	B	
⊙	XC-500-580-WT-BK	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	BK on WT
⊙	XC-1000-580-WT-BK	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	BK on WT
⊙	XC-1500-580-WT-BK	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	BK on WT
⊙	XC-500-580-OR-BK	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	BK on OR
⊙	XC-1000-580-OR-BK	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	BK on OR
⊙	XC-1500-580-OR-BK	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	BK on OR
⊙	XC-500-580-YL-BK	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	BK on YL
⊙	XC-1000-580-YL-BK	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	BK on YL
⊙	XC-1500-580-YL-BK	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	BK on YL
⊙	XC-500-580-CL-BK	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	BK on CL
⊙	XC-1000-580-CL-BK	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	BK on CL
⊙	XC-1500-580-CL-BK	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	BK on CL
⊙	XC-500-580-RD-WT	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	WT on RD
⊙	XC-1000-580-RD-WT	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	WT on RD
⊙	XC-1500-580-RD-WT	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	WT on RD
⊙	XC-500-580-GN-WT	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	WT on GN
⊙	XC-1000-580-GN-WT	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	WT on GN
⊙	XC-1500-580-GN-WT	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	WT on GN
⊙	XC-500-580-BL-WT	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	WT on BL
⊙	XC-1000-580-BL-WT	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	WT on BL
⊙	XC-1500-580-BL-WT	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	WT on BL
⊙	XC-500-580-WT-RD	1 roll (cont.)	30 ft.	0.500	9.14m	12.70m	RD on WT
⊙	XC-1000-580-WT-RD	1 roll (cont.)	30 ft.	1.000	9.14m	25.40m	RD on WT
⊙	XC-1500-580-WT-RD	1 roll (cont.)	30 ft.	1.500	9.14m	38.10m	RD on WT

IDXPERT™ Handheld Labeler


NEW FROM BRADY



Wire & Cable Markers – Self-Laminating

- Printer automatically “multiple repeats” your text in the white print area
- B-427 Vinyl Self-Laminating material, resistant to water, oil, solvents and abrasion
- UL recognized
- Temp range -94°F to 158°F (-70C to 70C)

Diagram



Wire Gauge*	Max Wire Diameter	Diagram	Part Number	Qty. per Cartridge	Dimensions (in.)			Dimensions (mm)			Color
					A	B	C	A	B	C	
16-10 Gauge	.16" (4mm)	▶	XSL-11-427	500	0.500	0.750	0.375	19.05m	19.05mm	9.53mm	BK on WT
16-10 Gauge	.16" (4mm)	▶	XSL-96-427	250	1.000	0.750	0.375	25.40m	19.05mm	9.53mm	BK on WT
12-10 Gauge	.21" (5mm)	▶	XSL-17-427	500	0.500	1.000	0.375	12.70 m	25.40mm	9.53mm	BK on WT
12-10 Gauge	.21" (5mm)	▶	XSL-18-427	250	0.750	1.000	0.375	19.05 m	25.40mm	9.53mm	BK on WT
12-10 Gauge	.21" (5mm)	▶	XSL-19-427	250	1.000	1.000	0.375	25.40 m	25.40mm	9.53mm	BK on WT
10-4 Gauge	.27" (7mm)	▶	XSL-102-427	250	0.500	1.250	0.375	12.70 m	31.75mm	9.53mm	BK on WT
10-4 Gauge	.27" (7mm)	▶	XSL-103-427	250	1.000	1.250	0.500	25.40 m	31.75mm	12.70mm	BK on WT
10-4 Gauge	.27" (7mm)	▶	XSL-115-427	250	1.500	1.250	0.500	38.10m	31.75mm	12.70mm	BK on WT
10-4 Gauge	.32" (8mm)	▶	XSL-29-427	500	0.500	1.500	0.500	12.70m	38.10mm	12.70mm	BK on WT
10-4 Gauge	.32" (8mm)	▶	XSL-30-427	250	0.750	1.500	0.500	19.05m	38.10mm	12.70mm	BK on WT
10-4 Gauge	.32" (8mm)	▶	XSL-31-427	250	1.000	1.500	0.500	25.40m	38.10mm	12.70mm	BK on WT
10-4 Gauge	.32" (8mm)	▶	XSL-31-427-YL-BK	250	1.000	1.500	0.500	25.40m	38.10mm	12.70mm	BK on YL
10-4 Gauge	.32" (8mm)	▶	XSL-32-427	250	1.500	1.500	0.500	38.10m	38.10mm	12.70mm	BK on WT
3 Gauge-2/0	.53" (14mm)	▶	XSL-21-427-YL-BK	100	1.000	2.500	0.750	25.40m	63.50mm	19.05mm	BK on WT
3 Gauge-2/0	.53" (14mm)	▶	XSL-21-427	100	1.000	2.500	0.750	25.40m	63.50mm	19.05mm	BK on YL
3 Gauge-2/0	.53" (14mm)	▶	XSL-116-427	100	1.500	2.500	0.750	38.10m	63.50mm	19.05mm	BK on WT
3/0-400 kcmil	.85" (22mm)	▶	XSL-23-427	100	1.000	4.000	1.000	25.40m	101.60m	25.40mm	BK on WT
3/0-400 kcmil	.85" (22mm)	▶	XSL-23-427-YL-BK	100	1.000	4.000	1.000	25.40m	101.60m	25.40mm	BK on YL
3/0-400 kcmil	.85" (22mm)	▶	XSL-33-427	100	1.500	4.000	1.000	38.10m	101.60m	25.40mm	BK on WT
500-900 kcmil	1.3" (33mm)	▶	XSL-34-427	50	1.500	6.000	1.500	38.10m	152.40m	38.10mm	BK on WT


*Approx based on AWG for THHN wire



Wire & Cable Markers – Adhesive Wrap-Around

- Printer automatically “multiple repeats” your text for 360° legend
- B-498 Vinyl Cloth Material with special adhesive stays put, but marker can be removed and reapplied if necessary
- UL recognized
- Temp Range -40°F to 175°F (-40C to 70C)

Diagram



Wire Gauge*	Max Wire Diameter	Diagram	Part Number	Quantity per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
					A	B	A	B	
22-16 Gauge	.11" (2.8mm)	★	X-7-498	350	0.500	0.500	12.70mm	12.70mm	BK on WT
16-10 Gauge	.16" (4mm)	★	X-11-498	350	0.500	0.750	19.05mm	12.70mm	BK on WT
12-10 Gauge	.21" (4mm)	★	X-19-498	250	1.000	1.000	25.40mm	25.40mm	BK on WT
12-10 Gauge	.21" (4mm)	★	X-18-498	250	0.750	1.000	19.05mm	25.40mm	BK on WT
10-4 Gauge	.27" (4mm)	★	X-103-498	250	1.000	1.250	25.40mm	31.75mm	BK on WT


*Approx based on AWG for THHN wire




Wire & Cable Markers – PermaSleeve™ Sleeves

- B-342 Heat Shrink Material (3:1 shrink ratio)
- Self-extinguishing—meets material & physical properties of MIL-DTL-23053/5C Class 1, MIL-M-81531, MIL-STD-202F, method 215 and UL 224
- Temp Range -67°F to 275°F (-55C to 135C)

Diagram



Diagram




Wire Gauge*	Wire Diameter Range	Diagram	Part Number	Quantity per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
					A	B	A	B	
1.015" MARKER LENGTH									
22-16 Gauge	.046-.110" (1.22-2.8mm)	●	XPS-125-1	100	1.015	0.235	25.78mm	5.96mm	BK on WT
18-12 Gauge	.062-.150" (1.6-3.8mm)	●	XPS-187-1	100	1.015	0.335	25.78mm	8.50mm	BK on WT
16-10 Gauge	.094-.215" (2.4-5.5mm)	●	XPS-250-1	100	1.015	0.439	25.78mm	11.15mm	BK on WT
12-6 Gauge	.125-.320" (3.2-8.1mm)	●	XPS-375-1	100	1.015	0.645	25.78mm	16.38mm	BK on WT
CONTINUOUS (CUT TO LENGTH)									
22-16 Gauge	.046-.110" (1.22-2.8mm)	□	XPS-125-CONT	1 roll (cont.)	12 ft.	0.235	3.65m	5.96mm	BK on WT
22-16 Gauge	.046-.110" (1.22-2.8mm)	□	XPS-125-CONT-YL-BK	1 roll (cont.)	12 ft.	0.235	3.65m	5.96mm	BK on YL
18-12 Gauge	.062-.150" (1.6-3.8mm)	□	XPS-187-CONT	1 roll (cont.)	12 ft.	0.335	3.65m	8.5mm	BK on WT
18-12 Gauge	.062-.150" (1.6-3.8mm)	□	XPS-187-CONT-YL-BK	1 roll (cont.)	12 ft.	0.335	3.65m	8.5mm	BK on YL
16-10 Gauge	.094-.215" (2.4-5.5mm)	□	XPS-250-CONT	1 roll (cont.)	12 ft.	0.439	3.65m	11.15mm	BK on WT
16-10 Gauge	.094-.215" (2.4-5.5mm)	□	XPS-250-CONT-YL-BK	1 roll (cont.)	12 ft.	0.439	3.65m	11.15mm	BK on YL
12-6 Gauge	.125-.320" (3.2-8.1mm)	□	XPS-375-CONT	1 roll (cont.)	12 ft.	0.645	3.65m	16.38mm	BK on WT

*Approx based on AWG for THHN wire

NEW FROM BRADY IDXPERT HANDHELD LABELER


IDXPERT™ Handheld Labeler



Terminal Block Markers

- These specially designed narrow-width markers automatically set to fixed spacing and separation between leg ends and automatically rotate to top-down orientation for perfect alignment on terminal blocks. Printer can auto-serialize to save additional time. B-428 Vinyl Cloth material.
- Temp Range -40°F to 175°F (-40C to 70C)
- UL Recognized

Diagram ●



Width of Strip	Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
				A	B	A	B	
.240" wide	●	XC-240-498	1 roll (cont.)	0.240	26 ft.	6.10mm	7.9m	BK on WT
.318" wide	●	XC-318-498	1 roll (cont.)	0.318	26 ft.	8.07mm	7.9m	BK on WT
.375" wide	●	XC-375-498	1 roll (cont.)	0.375	26 ft.	9.53mm	7.9m	BK on WT



Automation & Electrical Component Markers

Various sizes and label types for marking relays, solenoids, drive motors, switches or just about any component you have to label.

B-499 Nylon Cloth Material

- Permanent adhesive
- Pliable, for rough or smooth surfaces
- Temp Range -94°F to 194°F
- UL Recognized

B-428 Metalized Polyester

- Permanent adhesive
- Silver finish
- Temp Range -40°F to 176°F (-40C to 70C)
- UL Recognized

B-422 Gloss Polyester

- Permanent adhesive
- For smoother surfaces
- Temp Range -40°F to 212°F (-40C to 100C)
- UL Recognized

Diagram ▲




Diagram ▲





Diagram ○



Material Notes	Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
				A	B	A	B	
Permanent Nylon Cloth	▲	X-11-499	350	0.750	.500	19.05mm	12.70mm	BK on WT
Permanent Nylon Cloth	▲	X-84-499	350	0.900	.500	22.86mm	12.70mm	BK on WT
Metalized Polyester	▲	X-17-428-SV-BK	500	1.000	.500	25.40mm	12.70mm	BK on SV
Metalized Polyester (black border)	▲	X-24-428-SVBB-BK	500	1.130	.500	28.70mm	12.70mm	BK on SV
Metalized Polyester	▲	X-29-428-SV-BK	500	1.500	.500	38.10mm	12.70mm	BK on SV
Metalized Polyester	▲	X-20-428-SV-BK	100	2.000	1.000	50.80mm	25.40mm	BK on SV
Gloss Polyester	▲	X-19-422	250	1.000	1.000	25.40mm	25.40mm	BK on WT
Gloss Polyester	▲	X-30-422	250	1.500	.750	38.10mm	19.05mm	BK on WT
Gloss Polyester	○	XC-1000-422	1 roll (cont.)	30 ft.	1.000	9.14m	25.40mm	BK on WT



Bins & Storage I.D., General Industrial I.D.

A variety of sizes and extra-aggressive adhesives for bins, drawers, tools and equipment.

B-483 Ultra-Aggressive Polyester

- Permanent adhesive for textured/powder-coated surfaces
- Temp Range -40°F to 248°F (-40C to 120C)
- UL Recognized

B-580 Indoor/Outdoor Vinyl

- Permanent adhesive, good for rough surfaces
- Wide range of colors
- Temp Range -40°F to 248°F (-40C to 120C)

B-428 Metalized Polyester

- Permanent adhesive
- Silver finish
- Temp Range -40°F to 176°F (-40C to 70C)
- UL Recognized

Diagram ▲



Diagram ▲




Diagram ○





Diagram ✕



B-499 Nylon Cloth Material

- see top of page for material info

B-422 Gloss Polyester

- see top of page for material info

Material Notes	Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
				A	B	A	B	
Permanent Nylon Cloth (round label)	✕	X-82-499	350	.375" dia.		9.53mm dia.		BK on WT
Permanent Nylon Cloth (round label)	✕	X-83-499	350	.500" dia.		12.70mm dia.		BK on WT
Permanent Nylon Cloth	▲	X-11-499	350	0.750	0.500	19.05mm	12.70mm	BK on WT
Permanent Nylon Cloth	▲	X-84-499	500	0.900	0.500	22.86mm	12.70mm	BK on WT
Ultra Polyester for textured surfaces	▲	X-17-483	500	1.000	0.500	25.40mm	12.70mm	BK on WT
Ultra Polyester for textured surfaces	▲	X-61-483	100	2.000	0.500	50.80mm	12.70mm	BK on WT
Ultra Polyester for textured surfaces	▲	X-20-483	100	2.000	1.000	50.80mm	25.40mm	BK on WT
Ultra Polyester for textured surfaces	○	XC-1000-483	1 roll (cont.)	30 ft.	1.000	9.14mm	25.40mm	BK on WT
Metalized Polyester	▲	X-17-428-SV-BK	500	1.000	0.500	25.40mm	12.70mm	BK on SV
Metalized Polyester (black border)	▲	X-24-428-SVBB-BK	500	1.130	0.500	28.70mm	12.70mm	BK on SV
Metalized Polyester	▲	X-29-428-SV-BK	500	1.500	0.500	38.10mm	12.70mm	BK on SV
Metalized Polyester	▲	X-20-428-SV-BK	100	2.000	1.000	50.80mm	25.40mm	BK on SV
Gloss Polyester	▲	X-7-422	350	0.500	0.500	12.70mm	12.70mm	BK on WT
Gloss Polyester	▲	X-30-422	250	1.500	0.750	38.10mm	19.05mm	BK on WT
Gloss Polyester	▲	X-19-422	250	1.000	1.000	25.40mm	25.40mm	BK on WT
Indoor/Outdoor Vinyl (colored supplies)	○	XC-500-580-YL-BK	1 roll (cont.)	30 ft.	0.500	9.14mm	12.70mm	BK on YL*
Indoor/Outdoor Vinyl (colored supplies)	○	XC-1000-580-YL-BK	1 roll (cont.)	30 ft.	1.000	9.14mm	25.40mm	BK on YL*
Indoor/Outdoor Vinyl (colored supplies)	○	XC-1500-580-YL-BK	1 roll (cont.)	30 ft.	1.500	9.14mm	38.10mm	BK on YL*

*also available in Red, Orange, Green, Blue, White, and Clear— refer to Facility ID Tapes on Page 454

IDXPERT™ Handheld Labeler




Voice/Data Cable Markers


Ideal for marking data cabling, this cable marker's protected printing offers superior abrasion resistance and resistance to dirt, oils, solvents and water. Marker features a clear, non-printed area which wraps around and overlaminates the printed text. Printer automatically "multiple repeats" your text in the white print area. B-427 Vinyl Self Laminating material.

- Resistant to abrasion, water, oil and solvents
- Temp range -94°F to 158°F (-70C to 70C)
- UL recognized

Diagram ▾



Sized to Fit	Diagram	Part Number	# per Cartridge	Dimensions (in.)			Dimensions (mm)			Color
				A	B	C	A	B	C	
2 pair Fiber/Coaxial, Single/Multi Mode	▾	XSL-19-427	250	1.000	1.000	0.375	25.40mm	25.40mm	9.53mm	BK on WT
CAT-5, 4 pair UTP Copper	▾	XSL-102-427	250	0.500	1.250	0.375	12.70mm	31.75mm	9.53mm	BK on WT
CAT-5, 4 pair UTP Copper, Fiber, Coaxial	▾	XSL-103-427	250	1.000	1.250	0.500	25.40mm	31.75mm	12.70mm	BK on WT
CAT-5, 4 pair UTP Copper	▾	XSL-115-427	250	1.500	1.250	0.500	38.10mm	31.75mm	12.70mm	BK on WT
CAT-5, 4 pair UTP Copper	▾	XSL-29-427	500	0.500	1.500	0.500	12.70mm	38.10mm	12.70mm	BK on WT
CAT-5, 4 pair UTP Copper	▾	XSL-30-427	250	0.750	1.500	0.500	19.05mm	38.10mm	12.70mm	BK on WT
CAT-5, 4 pair UTP Copper, Fiber, Coaxial	▾	XSL-31-427	250	1.000	1.500	0.500	25.40mm	38.10mm	12.70mm	BK on WT
CAT-5, 4 pair UTP Copper, Fiber, Coaxial	▾	XSL-31-427-YL-BK	250	1.000	1.500	0.500	25.40mm	38.10mm	12.70mm	BK on YL
CAT-5, 4 pair UTP Copper, Fiber, Coaxial	▾	XSL-32-427	250	1.500	1.500	0.500	38.10mm	38.10mm	12.70mm	BK on WT
25 pair Copper, 4-12 pair Fiber, Coaxial	▾	XSL-21-427	100	1.000	2.500	0.750	25.40mm	63.50mm	19.05mm	BK on WT
25 pair Copper, 4-12 pair Fiber, Coaxial	▾	XSL-21-427-YL-BK	100	1.000	2.500	0.750	25.40mm	63.50mm	19.05mm	BK on YL
25 pair Copper, 4-12 pair Fiber, Coaxial	▾	XSL-116-427	100	1.500	2.500	0.750	38.10mm	63.50mm	19.05mm	BK on WT
50 pair Copper, 24 pair Fiber, Backbone	▾	XSL-23-427	100	1.000	4.000	1.000	25.40mm	101.60mm	25.40mm	BK on WT
50 pair Copper, 24 pair Fiber, Backbone	▾	XSL-23-427-YL-BK	100	1.000	4.000	1.000	25.40mm	101.60mm	25.40mm	BK on YL
50 pair Copper, 24 pair Fiber, Backbone	▾	XSL-33-427	100	1.500	4.000	1.000	38.10mm	101.60mm	25.40mm	BK on WT
100 pair Copper, 36 pair Fiber, Backbone	▾	XSL-34-427	50	1.500	6.000	1.500	38.10mm	152.40mm	38.10mm	BK on WT



Voice/Data Patch Panel, Outlet & Faceplate Markers

B422 Gloss Polyester

- Permanent adhesive for smoother surfaces
- Temp Range -40°F to 212°F (-40C to 100C)
- UL Recognized

Diagram ▲





Diagram ●



Application	Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
				A	B	A	B	
Label Each Port	▲	X-7-422	350	0.500	0.500	12.70mm	12.70mm	BK on WT
Label Multiple Ports on Cont. Tape	●	XC-375-422	1 roll (cont.)	30 ft.	0.375	9.14mm	9.53mm	BK on WT
Label Multiple Ports on Cont. Tape	●	XC-500-422	1 roll (cont.)	30 ft.	0.500	9.14mm	12.70mm	BK on WT
Label Faceplate	▲	X-17-422	500	1.000	0.500	25.40mm	12.70mm	BK on WT
Label Faceplate	▲	X-29-422	500	1.500	0.500	38.10mm	12.70mm	BK on WT



Voice/Data I.D. for Racks, Bays, Frames, Public Network & Data Centers

B-422 Gloss Polyester

- Permanent adhesive
- Temp Range -40°F to 212°F (-40C to 100C)
- UL Recognized

B-483 Ultra-Aggressive Polyester


- Permanent adhesive for textured/powder-coated surfaces
- Temp Range -40°F to 248°F (-40C to 120C)
- UL Recognized

B-580 Indoor/Outdoor Vinyl

- Permanent adhesive, good for rough surfaces
- Wide range of colors
- Temp Range -40°F to 248°F (-40C to 120C)

Diagram ▲
(see illustration above)

Diagram ●



Material Notes	Diagram	Part Number	Labels per Cartridge	Dimensions (in.)		Dimensions (mm)		Color
				A	B	A	B	
Ultra Polyester for textured surfaces	▲	X-17-483	500	1.000	0.500	25.40mm	12.70mm	BK on WT
Ultra Polyester for textured surfaces	▲	X-61-483	100	2.000	0.500	50.80mm	12.70mm	BK on WT
Ultra Polyester for textured surfaces	▲	X-20-483	100	2.000	1.000	50.80mm	25.40mm	BK on WT
Ultra Polyester for textured surfaces	●	XC-1000-483	1 roll (cont.)	30 ft.	1.000	9.14mm	25.40mm	BK on WT
Gloss Polyester	▲	X-17-422	500	1.000	0.500	25.40mm	12.70mm	BK on WT
Gloss Polyester	▲	X-29-422	500	1.500	0.500	38.10mm	12.70mm	BK on WT
Gloss Polyester	▲	X-30-422	250	1.500	0.750	38.10mm	19.05mm	BK on WT
Gloss Polyester	▲	X-19-422	250	1.000	1.000	25.40mm	25.40mm	BK on WT
Gloss Polyester	●	XC-1000-422	1 roll (cont.)	30 ft.	1.000	9.14mm	25.40mm	BK on WT
Indoor/Outdoor Vinyl (colored supplies)	●	XC-500-580-YL-BK	1 roll (cont.)	30 ft.	0.500	9.14mm	12.70mm	BK on YL*
Indoor/Outdoor Vinyl (colored supplies)	●	XC-1000-580-YL-BK	1 roll (cont.)	30 ft.	1.000	9.14mm	25.40mm	BK on YL*
Indoor/Outdoor Vinyl (colored supplies)	●	XC-1500-580-YL-BK	1 roll (cont.)	30 ft.	1.500	9.14mm	38.10mm	BK on YL*

*also available in Red, Orange, Green, Blue, White, and Clear— refer to Facility ID Tapes on Page 454.